

FaceStation 2

Terminale di riconoscimento facciale intelligente



FaceStation 2 è il terminale di riconoscimento facciale più avanzato che offre molte delle migliori funzionalità al mondo. Dotato dell'ultima innovazione nella biometria facciale, FaceStation 2 offre velocità, precisione e livello di sicurezza senza eguali.

Con l'ingegneria ottica brevettata FaceStation 2 raggiunge fino a 25.000 lx di illuminamento operativo che, a sua volta, porta una sicurezza a tutto tondo indipendentemente dalle condizioni di illuminazione.

Inserito in una struttura progettata ergonomicamente, FaceStation 2 offre prestazioni e usabilità eccezionali per diversi siti di controllo accessi e presenze, grandi o piccoli.

Features

- 
Ultra Performance
 - Matching Speed: 1:3,000 match/sec
 - * Group Matching: 1:5,000 match/sec
 - User Capacity: Max 30,000 users (1:1), 3,000 users (1:N)

- 
Highest Operating Illuminance
 - Operating illuminance from 0 lx to 25,000 lx
 - Highest operating illuminance available
 - Covers complete darkness to all indoor lighting conditions

- 
Enhanced Security
 - Live face detection: IR-based image analysis to prevent spoofing by printed images and LCDs
 - Enhanced security by Android 5.0 Lollipop
 - High quality Image log

- 
Multi RFID Card Reading
 - LF(125KHz), HF(13.56MHz) dual-band
 - Reads all card types that HID multiCLASS supports (EM/HID Prox/MIFARE/ICLASS/DESFire/FeliCa/NFC)

- 
Ergonomics & User Convenience
 - Extended height range: 145cm – 210cm
 - Tilt-type bracket for wheelchair persons & children
 - Android 5.0 Lollipop based intuitive GUI
 - Improved face enrolment procedure

Specifications

Category	Features	FS2-D	FS2-AWB
Credential	Biometric	Face	
	RF Options	125kHz: EM 13.56MHz: MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, NFC	(Includes all FS2-D's RF types) 125kHz:HID Prox 13.56MHz: ICLASS SE/SR 2.4GHz: BLE
	RF read range*	MIFARE/DESFire/ICLASS : 50 mm EM/HID Prox/Felica: 30 mm, BLE: 50 mm	
General	CPU	1.4 GHz Quad Core	
	Memory	8GB Flash + 1GB RAM	
	LCD type	4" color TFT LCD	
	LCD resolution	800 x 480 pixels	
	IR LED	140 ea	
	Sound	24 bit Voice DSP (echo cancellation)	
	Operating temperature	-20°C ~ 50°C	
	Operating humidity	0% ~ 80%, non-condensing	
	Dimensions (W x H x D)	141 mm x 164 mm x 125 mm	
	Weight	Device: 548g, Bracket: 74g (incl. washer and bolt)	
Face	Certificates	CE, FCC, KC, RoHS, REACH, WEEE, BT SIG	
	Power	DC 24V 2.5 A	
Capacity	Image dimension	720 x 480 pixels	
	Live Face Detection	Supported	
Interfaces	Max. User	30,000 (1:1), 3,000(1:N)	
	Max. Log	5,000,000 (text), 50,000 (Image)	
	Wi-Fi	IEEE 802.11 b/g (FS2-AWB only)	
	Ethernet	Supported (10/100/1000 Mbps, auto MDI/MDI-X)	
	RS-485	1ch Host or Slave (Selectable)	
	Wiegand	1ch In and 1ch Out	
	TTL Input	2 Inputs	
	Relay	1 Relay	
	USB	USB 2.0 (Host)	
	Tamper	Supported	
Video Phone	SIP-based VoIP (Video + Voice)		

System Configurations
